

Genesis Solid & Perforated Panel



Triad's 5000 lb. Rated Panel

Load Ratings Solid & Perforated*

 Rolling Concentrated
 Ultimate
 Uniform

 Imperial (lbs)
 3000**
 5000
 10,000
 20,000

 Metric (kg)
 1350**
 1866
 4500
 9000

*CISCA & F.A.T tested



Pedestals

Pedestal assemblies when secured to the subfloor with adhesive, shall be capable of withstanding the following loads without anchors, panels or other supports in place.

- Overturning moment of 1,000 inchpounds/450 kg.
- Axial load of 10,000 lbs./4500 kg.



Stringer System

Stringers capable, without panels in place, capable of supporting a concentrated load of 2,500 lbs./450 kg. at mid-span on a one square inch indentor with a permanent set not to exceed .010".



PANEL TYPE	MODEL	LOAD RATING	AVAILABLE FEATURES	COMPATIBILITY
Solid Genesis Panel	Imperial 40TISD 50TISD	Concentrated Load 4000 & 5000 lbs Rolling Load 3000 lbs** Ultimate load 10,000 lbs Uniform Load 20,000 lbs. Per Independent CISCA Test **Test Equipment Limit	OPTIONAL: Corner Lock Dual Handles Horizontal & vertical levelers	Genesis Floor Systems
Perforated Panel	Imperial G30TPD	Concentrated Load 1500-3000 lbs Rolling Load 3000 lbs Ultimate load 10,000 lbs Uniform Load 20,000 lbs. Per Independent CISCA Test	Size: 24" x 24"	

TRIAD STATIC DISSAPATIVE TEXTURED POWDERPLATE COATINGS





Grey Flek

These color samples are representative only and will vary from the actual color depending on the computer monitor or printer used to view them. For accurate color, gloss and texture sample contact Triad. Additional colors and coatings are available upon request, call for pricing.

Additional Triad® Products







HyBrid Panel



Stainless Steel Panel



Genesis Cleanroom panel



Rolling Load Aisle Protector









